

Stage Lighting Equipment Supplier Expert

# USER'S MANUAL

## **LED Flat Par 5x12W RGBW Light**



#### Maintenance

- 1. Please keep the light in dryness and avoiding use in wet place.
- 2. Using intermittenly can be extended the life.
- 3.Attention to clean the fan and lens usually in order to get the ventilating effects and lighting effects better.
- 4. Please do not wipe the crust using organic menstruum for avoid to damaged the product.

#### Statement

The product has well capability and intact packing when leave factory, All of the user should comply with above warning item and manual , any misuse cause of the damages are not included in our guarantee, and also can't be responsible for any malfunction & problem owing to ignore the manual. Please forgive that we will not be notice for technical change


#### Attention Item

- 1. For guarantee the life of product, please do not put it on the wet place and not use it the place over 40 degree.
- 2.Please don't lay the product on the un-fixable or shakable place.

- 3. Ask for the professional to maintain the product in order to avoid the danger of get an electric shock.
- 4.Power supply should not be changed over +&-10% while the light is using, it will be decreased the life of lamp if the power is too high, but it will be influenced the luminosity if the power is too low.
- 5. After power off, if it is need used again, please cool down over 20 minuter.
- 6. Please look round the manual for ensure the product can be used normally.

## **Display Control Instruction**

Welcome to use our light. The light uses energy-saving LED, long Product life, shockproof, dustproof, DMX receiver and self-running feature, which can produce a variety of vivid lighting effects, easy to operate, suitable for all types of entertainment decoration, architectural lighting industry.



Instructions:Press the function key A cycled out the eight different function effects, digital tube first two digits on behalf of which the current function (see menu). The last two digits represent the functions in which the address code or speed parameters. Press the B or C key to modify the parameter values. Press the D key to confirm.

### **Product Introduction**

- Power Supply:AC90--275V,50--60HZ
- Power consumption:84W
- Fixing lamp:LED 7×12W RGBW
- DMX-Control-channels:7 DMX Channels
- Shuttle:Flash rate:0--10HZ
- Dimmer:0-100% mechanic dimmer
- Long Lifespan LEDs(more than 60,000 hours)
- Product size: 17.9\*11.3\*17.8 CM
- Product weight: 0.9 KG

## **DMX Channel Summary-7 Channels Mode**

Channel	Value	Function
1.	0-255	R,G,B,W total dimming,linear dimming form dark to light
2.	0-255	Red dimming,Linear dimming form dark to Bright
3.	0-255	Green dimming,Linear dimming form dark to Bright
4.	0-255	Blue dimming,Linear dimming form dark to Bright
5.	0-255	White dimming,Linear dimming form dark to Bright
6.	51-99	Auto Mode 1
	100-150	Auto Mode 2
	151-200	Auto Mode 3
	201-255	Sound Mode

7.	0-255	Strobe -RBGW (when CH6 in 0-50)
		Function Speed Adjustment -CH6

**Display Control Instruction** 

No	Display Control Instruction				
INO	Display	Function			
1.	a001-a512	7 channel address code,			
2.	Rfof-Rfon	Wireless remote control switch on /off			
3.	R000-r255	Red dimming,			
4.	G000-g25	Green dimming,			
	5				
5.	B000-b25	Blue dimming,			
	5				
6.	U000-U25	White dimming,			
	5				
7.	Fk01-fk99	Strobe			
8.	Cl01-cl12	Auto run mod 1			
9.	CcO1-cc99	Auto run mod 2			
10.	De01-de99	Auto run mod 3			
11.	Cp01-cp99	Auto run mod 4			

