



Stage Lighting Equipment Supplier Expert

WELCOME TO JOIN US

USER'S MANUAL

100W LED 6in1 RGBWA+UV COB Blinder



Maintenance

1. Please keep the light in dryness and avoiding use in wet place.
2. Using intermittently can be extended the life.
3. Attention to clean the fan and lens usually in order to get the ventilating effects and lighting effects better.
4. Please do not wipe the crust using organic menstruum for avoid to damaged the product.

Statement

The product has well capability and intact packing when leave factory, All of the user should comply with above warning item and manual, any misuse cause of the damages are not included in our guarantee, and also can't be responsible for any malfunction & problem owing to ignore the manual.

Please forgive that we will not be notice for technical change

Attention Item

1. For guarantee the life of product, please do not put it on the wet place and not use it the place over 40 degree.
2. Please don't lay the product on the un-fixable or shakable place.
3. Ask for the professional to maintain the product in order to avoid the danger of get an electric shock.
4. Power supply should not be changed over +&-10% while the light is using, it will be decreased the life

- of lamp if the power is too high, but it will be influenced the luminosity if the power is too low.
5. After power off, if it is need used again, please cool down over 20 minutes.
6. Please look round the manual for ensure the product can be used normally.

DMX Channel Summary-6 Channels Mode d001

Channel	Value	Function
CH1	0-255	Red light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment
CH2	0-255	Green light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment
CH3	0-255	Blue light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment
CH4	0-255	White light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment
CH5	0-255	Amber light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment
CH6	0-255	Violet light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment

DMX Channel Summary-10 Channels Mode A001

Channel	Value	Function
CH1	0-255	Total dimming, from dark to bright
CH2	0-255	Red light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment
CH3	0-255	Green light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment
CH4	0-255	Blue light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment

CH5	0-255	White light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment
CH6	0-255	Amber light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment
CH7	0-255	Violet light color control, channel value of 0 for the closed light, 1~255 for the red light adjustment
CH8	0-255	Total strobe, 005-255 from slow to fast
CH9	0-50 51-100 101-150 151-200 201-250 251-255	NO Effect Preset color Auto Mode 1 Auto Mode 2 Auto Mode 3 Sound Mode
CH10	0-255	CH9 Functional speed, from slow to fast

Display Control Instruction

Display	Value	Function
d001	001- 512	DMX512 address code set to 4-channel mode
R001	001- 512	DMX512 address code set -8 channel mode
r255	000 - 255	Red dimming, from dark to bright
G255	000 - 255	Green dimming, from dark to bright
b255	000 - 255	Blue dimming, from dark to bright
u255	000 - 255	White dimming, from dark to bright
Y255	000 - 255	Amber dimming, from dark to bright
P255	000 - 255	Violet dimming, from dark to bright
FH99	000 -099	strobe, speed from slow to fast
CL08	01-08	Color present
CC99	01-99	Jump effect Auto Mode 1
dE99	01-99	Gradient effect Auto Mode 2
CP99	01-99	Pulse effect Auto Mode 3
SU01	01-09	Sound control

Display Control Instruction

Welcome to use our light. The light uses energy-saving LED, long Product life, shockproof, dustproof, DMX receiver and self-running feature, which can produce a variety of vivid lighting effects, easy to operate, suitable for all types of entertainment decoration, architectural lighting industry.


A:Function

B:Up

C:Down

D:Enter

E:LED Display



Instructions: Press the function key A cycled out the eight different function effects, digital tube first two digits on behalf of which the current function (see menu). The last two digits represent the functions in which the address code or speed parameters. Press the B or C key to modify the parameter values. Press the D key to confirm.

Product Introduction

- * Power Supply: AC90--275V, 50--60HZ
- * Power consumption: 100W
- * Fixing lamp: LED 100W 6in1 RGBWA+UV mixed
- * DMX-Control-channels: 6/10 DMX Channels
- * Shuttle: Flash rate: 0--10HZ
- * Dimmer: 0-100% mechanic dimmer
- * Long Lifespan LEDs (more than 60,000 hours)

[HTTP://WWW.SHEHDS.COM/](http://www.shehds.com/)